

## Simple IVR Api Request

http://125.16.147.178/VoicenSMS/webresources/CreateOBDCampaignPost

```
{
  "sourcetype": "0",
  "campaigntype": "3",
  "filetype": "2",
  "voicefile": "HoldtestrEQUEST.wav",
  "ukey": "PkmKjuTQo6A2Mqkcwb9F0EL4A",
  "serviceno": "9898",
  "ivrtemplateid": "1",
  "retryatmpt": "3",
  "retryduration": "15",
  "msisdn": ["98xxxxxxxx"],
  "msisdnlist":
  [{"phoneno":"98xxxxxxxx","callid":"65","altno1":"","altno2":"","text1":"","text2":"","text3":"","text4":"","text5":"","text6":"","text7":"","text8":"","text9":"","text10":""}]
}
```

Success Response :

```
{
  "status":"success",
  "leadid":2511,
  "inserted":1,
  "rejected":0,
  "refno":[{"98xxxxxxxx":"2511_3204_113229_2018-09-01_154413"}]
}
```

Failure Response :

```
{
  "status":"failure",
  "value":"ukey is invalid",
  "error_code":"Error_1010"
}
```

Description :

1. sourcetype : 0:for getting data from <msisdn>,1: for getting data from <tableName> with <connID>,2: for getting data from excel file
2. campaigntype : 3- Promotional,4- Transactional
3. filetype : 2(Not to be Changed)
4. voicefile : Voice File Name
5. serviceno : Service Number
6. ivrtemplateid : 1-Simple,2-DTMF,3-Latching and for Custom other
7. retryatmpt : Retry Attempts
8. retryduration : Retry Dur. 0=immediate,15 mins,30 mins ,60=1hour
9. latchagentlist : Agent latch List
10. latchdialmode : 1 (Not to be changed)
11. waitdurlatch : Wait duration
12. latchvoicefile : Latch Voice File Name
13. respretrylatch : Response Retry
14. msisdn : Phone No
15. dtmflength : Max Dtmf Length
16. waitduration : Maximum Value is 8 Secs
17. connid : Connection ID of ODBC
18. tablename : 3rd Party Call ID Table Name
19. thirdpartycampid : 3rd Party Campaign ID
20. xlsfilepath : Excel File Path
21. xlsfilename : Excel File Name
22. isleaddataincr : true: for incrementing data in provided lead id & false: Default
23. localleadid : 0: New Campaign & any other for previous
24. enablesuccessmsg : 0: False, 1: True
25. successtemplateid : Template ID for Success Message
26. enablefailuremsg : 0: False, 1: True
27. failuretemplateid : Template ID for Failure Message
28. sendnow : 0: true, 1: Schedule Lead
29. schddate : Date for scheduling(Works only when the value of sendNow is 1)

29. schddate : Date for scheduling(Works only when the value of sendNow is 1)  
30. isdistributed : true for sending data in desired platforms, false for normal load balancing  
31. platformcsv : Platform IDs in comma separated format  
32. msisdnlist : use for call ID and phoneNo  
[{"phoneno":"98xxxxxxx","callid":"65656","altno1":"","altno2":"","text1":"","....."}]